

## **Goliath End of Line Systems**

# **Filling & Capping Systems**

## **Benchtop Fillers**

### **AdaptaFil™ Semi-Automatic Benchtop Filler**

The AdaptaFil™ is revolutionary new semi-automatic Benchtop filler that offers features and versatility typically only found in fully automatic equipment. The AdaptaFil™ Benchtop's patent pending technology features four easy-changeover metering system, electronic networking capabilities and sophisticated, user-friendly controls all in a small and sleek stainless steel package.

You have the option of switching between a peristaltic, piston, gear, or lobe pump while utilizing the same base. This eliminates the need for multiple machines saving money and space. The changeover is completely tool-less and can be done in 5 minutes or less. The multiple pump options make this machine ideal for filling mLs to gallons and product viscosities that range from aqueous to viscous.

The HMI touch screen allows you to create, copy, and save text based recipes which dramatically reduces your set-up time as you switch between products, fill volumes, or container sizes because it is digitally controlled-no manual adjustments needed.

Additional features such as weight compensation, adjustable batch counting, and clean room design are also available.



### **AB Series Medium Duty Filling Machines**

The Filamatic AB Series Benchtop is a semi-automatic medium duty filler, ideal for repetitive dispensing of liquids from water-thin to viscous, molten products, and products with small particulates. The AB Series can accommodate fill volumes ranging from .05 to 260mL with the ability to mix and match pumps and nozzles for optimal versatility and flexibility.

This single nozzle filling machine incorporates a variable speed electrical gear motor drive, which turns the crankshaft that drives a volumetric piston pump known as a "Filling Unit". The Filling Units are accessories offered to dispense a wide range of liquids and are made from either glass or Stainless Steel.

The AB Series is offered in three models which operate at a maximum rate of 85 RPM, 35RPM, and 23 RPM. Designs are available for OEM Applications as well as CE Mark certified, and air operated models for hazardous environments.



**For more information or to discuss your specific application call  
Sales @ 067-37893 / 087-1222816**

**GOLIATH PACKAGING SYSTEMS LTD.**

92 Silver Street, Nenagh, Co. Tipperary

Phone: 353-67-37893 Fax: 353-67-34794 E-mail: [info@goliath.ie](mailto:info@goliath.ie)

