

Goliath End Of Line Automation

Goliath Semi Auto—Rotary Arm

Flat base area to indicate pallet placing area – allows pallets to be placed accurately using manual pallet trucks as well as fork lifts.

Rotating arm has safety cage fitted around film carriage which stops immediately if it detects an object/person. Fixed barriers and light barriers available also (not supplied with standard machine)

PALLET DIMENSIONS

Max 1.200 x 1.200 x 2.100 (h) mm.

Min 600 x 600 x 500 (h) mm.

FILM CARRIAGE BELT DRIVEN WITH THE FOLLOWING POSSIBILITIES:

Film pre-stretch with LP 200% motorizes power pre-stretch
Photoelectric cell to read pallet height

ELECTRICAL CONTROL PANEL WITH THE FOLLOWING FUNCTIONS:

Independent top & bottom layers adjustment with timers
Manual and automatic working cycle with **2 wrapping programmes**

- Carriage only up
- Carriage up + down

Inverter to control: **Adjustable speed (6-12 rpm)**

Soft Start - Fix Stop of the rotating arm, motorized with clutched motor chain driven.

Safety Panels all around the RA-S with anti-intrusion electronic system in front of the unit stopping the machine as soon as circuit interrupted

Inspection mirror of the “non visible area” with the pallet in position from operational bottoms.

Video & Acoustic alarm before working cycle starts

Hot painting with epoxy system

Standard power supply 400 Volt – 50 Hz – 3Phases



For more information or to discuss your specific application call
Sales @ 067-37893 / 087-1222816

GOLIATH PACKAGING SYSTEMS LTD.

92 Silver Street, Nenagh, Co. Tipperary

Phone: 353-67-37893 Fax: 353-67-34794 E-mail: info@goliath.ie www.goliath.ie

