

Goliath End of Line Automation

Bag Filling

Stick Pack HBV-4

Looking for flexibility in your StickPack needs? Our versatile multi-lane HBV-4 StickPack machines can accommodate from 1 to 14 lanes to form different shapes of StickPack pouches.

Designed to pack powders, dense, fine, loose and particulate materials as well as liquids and semiliquids into StickPack bags and to accommodate different bag shapes including pour spouts, tear notches and easy-open system.

Easy change-over® option enables to pack into different bag widths with fast change-over times. Want peace of mind? Make the HBV-4 your next investment and Stick With the Best™

Performance

Speed

Minimum: 5 BPM

Maximum: 75 cycles/min *

	Minimum	Maximum
Width	15 mm	50 mm
Length	50 mm	200 mm
Film width		560 mm

Bag styles: Stick pack

*Note: Actual speeds are dependent on the product characteristics and quality, film quality, operator, product in-feed and ambient conditions. Actual speeds will be confirmed upon trials with original film and product.

Construction:	Stainless steel or painted steel
Drive:	Main drive (cross jaws): stepper motor
Machine dimensions:	1450 mm wide x 1660 mm deep x 1800 mm high (without filler)
Electrical requirements:	400V, 3 phase, 50Hz or 480 V, 3 phase, 60Hz or 220, single phase, 50/60HZ 6,5 kVA
Air requirements:	6 bars (0,6 Mpa), dry and oil free air 4 NL / cycle
Film reel:	Max. outside diameter 400 mm, Ø75 mm core
Control system:	Siemens S7-200 or Allen Bradley Color touch screen panel

**For more information or to discuss your specific application call
Sales @ 067-37893 / 087-1222816**



GOLIATH PACKAGING SYSTEMS LTD.

92 Silver Street, Nenagh, Co. Tipperary

Phone: 353-67-37893 Fax: 353-67-34794 E-mail: info@goliath.ie www.goliath.ie

