

Goliath End of Line Automation Labeling & Coding Systems

Reliable, Accurate, Compact: The ALS 104

Automatic Label Applicator machines are used to apply pre-printed, self-adhesive (pressure-sensitive) labels to products, accurately and reliably every time. Variable over-printing can be accommodated by fitting an optional hot-foil or thermal transfer coder. Label applicators can be mounted above, to the side or upside-down underneath a conveyor, to achieve the best labelling position.

Different shaped products will require labels to be applied in different ways, so ALS produces applicator modules to suit all common applications. All models are available in left and right handed versions and can be engineered to integrate with your existing line equipment.

The **ALS 104** is our entry-level priced labelling unit in the "compact class".

Your benefits:

- Top quality for standard applications
- Excellent price-performance ratio
- Various application edges
- Application speed of up to 30 m/min
- Automatic continuous adjustment to actual production line speed with APSF function
- Auto-compensation for missing labels on web
- Braked label unwind for constant web tension gives consistent accuracy at the dispense edge
- 3 mounting positions for easy integration on line

The High-Performance ALS 204 and ALS 206

In addition to the strong features of the ALS 104, these applicators offer even more benefits:

- Highest quality for demanding applications
- Application speed of up to 40 m/min
- Unbeatable flexibility with the various add-on application units available
- Easy maintenance and quick control with user-friendly central remote control function
- Zero down-time with 2 units labeling non-stop in a "master/slave" configuration
- RFID capability possible as an option
- Low Cost, Compact Size, High Build Quality

With cast-aluminium housing, the ALS Compact Class is an industrial-capable range at an extremely affordable price. They are fast and durable, even with the most demanding requirements in round-the-clock operations.

User-Friendly

The 360° rotatable multifunctional display with intuitive menu structure is integrated. The machine can be optionally operated remotely by a cable connection to an additional remote control display.

Flexible in Use

The ALS family enables top, side and underneath labelling with three different mounting options, absolutely in line with your requirements. The "L"-shaped dispensing edge, which can be rotated by up to 90° and locked in position, ensures even more flexibility.

Multiple Application Methods

Various application devices are available for the ALS204/206 to suit your specific product labelling requirements, depending on speed, position and orientation. Options include: direct apply/wipe-on, blow-on, tamp-on, tamp-blow.

**For More information or to discuss your specific application call
Sales @ 067-37893 / 087-1222816**



GOLIATH PACKAGING SYSTEMS LTD.

92 Silver Street, Nenagh, Co. Tipperary

Phone: 353-67-37893 Fax: 353-67-34794 E-mail: info@goliath.ie www.goliath.ie

